



Simple and easy appearance, in line with contemporary aesthetic concept. The product has the structure and appearance design patent. The lamp body adopts high-pressure cast aluminum and aluminum alloy, the surface is coated with outdoor used powder, double anti-corrosion to extend service life. This lawn lamp series uses LED. High efficiency constant current driver, ensure the light source is maximum used.

**FIELDS OF APPLICATION**

Office & Education, offices, open-plan offices, conference rooms, conference rooms, reception areas, counters, galleries, hotels, restaurants, living spaces

IEC 62717 LED-modules for general lighting – Performance requirements  
IEC 62722-2-1 Particular requirements for LED luminaires

High Lumen Efficacy 115lm/W  
Body - Die cast aluminum housing with solvent free powder coating  
Diffuser - PMMA polycarbonate pattern lens.  
Glowing Wire Test - 850°  
Temperature - ta=20 °C ~ ta max=50 °C  
Class - III

Model --- **3343**



**A - Ø 102-120mm**

Default Available



Product Assistant Chart

**3343** X X X X X

Size A

Driver 0 1 2 3 4  
On/Off Dali Dimmable Phase Dimming 1-10

Beam Angle 17.6° 27.8° 34.2° 44.7°

Kelvin 27 30 40 50 60  
2700K 3000K 4000K 5000K 6000K



Finishing W B  
white black

Wattage 8 10 12 15 20 25 30 35

Lighting Customization Solution can offer you modifications for environment with higher options as a customized product.

IP44 COB McA Step 3 220~240V

Relative spectral perception of brightness and melanopic effect



LED life time		Operating time 1.000 h											
Lamp Lumen Maintenance Factor		1	10	20	30	40	50	60	70	80	90	100	
Lamp Survival Factor		1	1	1	1	1	1	1	1	0.99	0.99	0.99	
L80	50.000 h	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.60	
		LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.98	
L80	100.000 h	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82	0.80
		LSF	1	1	1	1	1	1	1	0.99	0.99	0.99	0.99



LED



series wiring



LM-80



Flicker FREE