



Simple and easy appearance, in line with contemporary aesthetic concept. The product has the structure and appearance design patent. The lamp body adopts high-pressure cast aluminum and aluminum alloy, the surface is coated with outdoor used powder, double anti-corrosion to extend service life. This lawn lamp series uses LED. High efficiency constant current driver, ensure the light source is maximum used.

FIELDS OF APPLICATION

Office & Education, offices, open-plan offices, conference rooms, conference rooms, reception areas, counters, galleries, hotels, restaurants, living spaces

IEC 62717 LED-modules for general lighting – Performance requirements IEC 62722-2-1 Particular requirements for LED luminaires

High Lumen Efficacy 115lm/W

Body - Die cast aluminum housing with solvent free powder coating

Diffuser - PMMA polycarbonate pattern lens.


Glowing Wire Test - 850°


Temperature - ta=20 °C ~ ta max=50 °C

Class - III

Model --- GD025








Default Available


Product Assistant Chart

GD025 XXXXX



Lighting Customization Solution can offer you modifications for environment with higher options as a customized product.

220~240V







TRIDONIC


17.6°			
	Diameter(m)		
	0.47	1.5m 3054lx	
K/XHHK/X	0.70	2.25m 1357lx	
	1.09	3.5m 561lx	
MAH	1.24	4.0m 429lx	
	1.55	5.0m 275lx	
20' 10' 0' 10' 20'			


McA Step 3

COB









LED life	time		Operating time 1.000 h										
Lamp Lumen Maintenance Factor Lamp Survival Factor			1	10	20	30	40	50	60	70	80	90	100
			1	1	1	1	1	1	1	1	0.99	0.99	0.99
L80	50,000 b	LLMF	1	0.96	0.92	0.88	0.84	0.80	0.76	0.72	0.68	0.64	0.60
	50.000 h	LSF	1	1	1	1	1	1	0.99	0.99	0.99	0.99	0.98
L80	400 000 b	LLMF	1	0.98	0.96	0.94	0.92	0.90	0.88	0.86	0.84	0.82	0.80
	100.000 h	LSE	1	1	1	1	1	1	1	n aa	n ga	n aa	n aa























1.5m 1284lx

3.5m 236lx

4.0m 181lx

